

# Triangular Wave Technologies Accessories for Deposit Control System

## ACCESSORIES for DEPOSIT CONTROL SYSTEMS

<i>TWT-CSE-0227</i>	<i>Copper pipe signal enhancer</i> For copper pipes up totwo inches ( 2" ) in diameter
<i>TWT-CSE-0229</i>	<i>Copper pipe signal enhancer</i> For copper pipes up tofour inches ( 4" ) in diameter
<i>TWT-WS-55</i>	55' Wire Spool
<i>TWT-WS-125</i>	125' Wire Spool
<i>TWT-WST-55</i>	55' Wire Spool-Teflon Coated
<i>TWT-WST-125</i>	125' Wire Spool-Teflon Coated
<i>TWT-PT-10</i>	Set of 10 Plastic Ties
<i>TWT-8449-25</i>	Flex Tubing–25 ft.
<i>TWT-8449-50</i>	Flex Tubing–50 ft.
<i>TWT-8449-100</i>	Flex Tubing–100 ft.
<i>TWT-LP-70F</i>	CSE Black Box (to mount & enclose a CSE unit)
<i>TWT-8398 (2 pk)</i>	Connectors for Flex Tubing/BIack Box - Qty 2 for each CSE unit
<i>TWT-HTK</i>	Hardness Test Kit
<i>TWT-COND</i>	Portable Conductivity Meter
<i>TWT-TDS</i>	Portable Total Dissolved Solids Meter

